

Declaration of Performace

According to Regulation (EU) No 305/2011 of 9 March 2011

N°: 2013/1

1	Product type for identification	Dry-pressed ceramic tiles with low water absorption of 0,5% < E _b ≤ 3%	
2	Intended use	For floor and wall coverings in indoor and outdoor areas	
3	Manufacturer	CE.SI. – Ceramica di Sirone S.p.A., via Don Minzoni ,19 Sirone	
4	System of assessment and verification of constancy of performance	System 3 and 4	
5	Name and number of the office for the control	Centro Ceramico di Bologna, via Martinelli 26, Bologna –N°1477	

6 Declared performace

Essential characteristics	Performance	Harmonized technical specification
Behaviour in fire	Classe A1 _{FL} /A1	EN 14411 : 2012 EN 14411 : 2012
Flexural tensile strength	> 1100 N (thickness ≥ 7,5 mm) > 700 N (thickness < 7,5 mm)	
Non – slip properties *	NPD	EN 14411 : 2012
Tactility "	NPD	EN 14411 : 2012
Thermal shock resistence	Resistence	EN 14411 : 2012
adhesive strength:		
Mortars containing cement type C2	≥ 1 N/mm²	EN 14411 : 2012
Durability in case of :		
- Application in indoor areas	Resistence	EN 14411 : 2012
- Application in outdoor areas	Resistence	EN 14411 : 2012
Delivery of dangerous substances:		
Cadmium***	Don't release	EN 14411 : 2012
Lead ***	Don't release	EN 14411 : 2012
voc	A+	EN ISO 16000-:2012-03-01

^{*} Necessary only when expressly required of the official regulations. For details refer to the pages of the catalogue

The performace of the product identified in point 1 is in conformity with the declared performace in point 6

This declaration of performace is issued under the sole responsability of the manufacturer identified in point 3

Signed for and on behalf of the manufacturer by:

Fumagalli Giuseppe, Presidente

Name and function

Sirone, 26/11/2013

place and date of issue

^{**}Only if it is necessary a surface with tactile effect or for blind people

^{***} Only needed if the material is in contact with food or when expressly required of the official regulations