

## **Declaration of Performance**

No. tona-BIII-001

1: Unique identification code of the product type:

Dry-pressed ceramic tiles, with water absorption E<sub>b</sub>> 10%

2: Intended use(s):

For internal wall

3: Name or registered trade mark, and conctact address of the manufacter:

Tonalite S.p.A.

Via Costa 8, 40019 Sant'Agata Bolognese - Italia

4: System(s) of assessment and verification of constancy of performance (AVCP):

Systems 4

5: Name and identification number of notified laboratory, if relevant:

Not relevant

6: Declared performances

Essential characteristics	<u>Performance</u>	Harmonised technical specification		
Reaction to fire	AI - AIFL			
Release of dangerous substance, for:	-			
Cadmium	NPD	EN 14411		
Lead	NPD			
Breaking strength:		1		
Thickness ≥ 7.5mm	>600 N			
Thickness < 7.5mm	>200 N			
Bond strength/adhesion, for:	NPD			
Durability for:				
Internal use	Pass			

The performance of the product identified in point 1 is in conformity with the declared performance in point 6. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 3.

Signed for and on behalf of the manufacterer by:

Eng. Pagani Paolo Production Manager

Place and date of issue

BURES

Sant'Agata Bolognese 30/11/2018