

ALABAMA ARTICO RECT 20X120

| REFERENCE | SIZE (cm) | THICKNESS (mm) | GROUP |
|----------------|-----------|----------------|-------|
| A032259 | 20x120 | 105,00 | |



DIMENSIONS AND SURFACE PROPERTIES

| | | |
|---|--------------|----------------------------------|
| Size, thickness, side straightness, flatness, orthogonality | UNE-EN 14411 | It accomplished all requirements |
|---|--------------|----------------------------------|

PHYSICAL PROPERTIES

| | | |
|--------------------------------------|-----------------|-------------------------|
| Water absorption capacity | EN ISO 10545-03 | < 0,5% |
| Flexion resistance | EN ISO 10545-04 | => 40 N/mm ² |
| Abrasion resistance (glazed Ceramic) | EN ISO 10545-07 | IV |
| Thermal shock resistance | EN ISO 10545-09 | It stands the test |
| Cracking resistance | EN ISO 10545-11 | It stands the test |
| Frost resistance | EN ISO 10545-12 | It stands the test |

CHEMICAL PROPERTIES

| | | |
|--|-----------------|----|
| Resistance to acids | EN ISO 10545-13 | GA |
| Resistance to alkalis | EN ISO 10545-13 | GA |
| Resistance to cleaning products | EN ISO 10545-13 | GA |
| Resistance to chemical products in swimming pool water | EN ISO 10545-13 | GA |
| Stains resistance | EN ISO 10545-14 | 5 |

ANTI-SLIP CHARACTERISTICS

| | | |
|------------------------|--------------|---------|
| Slip resistance (Rd) | UNE-ENV12633 | Class 2 |
| Slip resistance (R) | DIN 51130 | R10 |
| Slip resistance (DCOF) | ANSI A137,1 | 0,65 |