

GlamSatin

The Luminous Wallcovering

1. Description

GlamSatin is an extremely high-quality material that is able to evoke the shimmer and gentle movement of silk. The result of Glamora research, it is made up of a viscose fabric and has a mineral powder finish. With its exquisite iridescent embossing, it reflects light so every element portrayed takes shape in an extremely natural and visually expressive way.

2. Uses

GlamSatin is the ideal solution for vertical interior surfaces in residential, commercial and hospitality settings. The wallcovering can be used in both classic and contemporary spaces, residential or business settings or luxury hospitality. Its elegant weave makes this the perfect solution for intimate spaces such as bedrooms and shared spaces such as living areas. When used in workplace settings or spaces that are open to the public (restaurants, hotels, showrooms, conference rooms), it imbues a large wall surface with that elegant, resplendent world which inspires it.

3. Surface preparation

To apply a wallcovering correctly it is essential that you refer to the *Installation Manual*. This can be found inside the box and can also be downloaded from glamora.it from the page entitled Materials. Should you require further details, please contact our Customer Care Service.

Before starting, please make sure that the surface where you will be applying GlamSatin is perfectly smooth, flat and white. This surface must be completely dry, have a residual humidity level of less than 2.0%, and must be free of any signs of dirt, pencil marks, dust, grit and damp spots. Make sure that there are no drafts in the space where the wallcovering will be applied and that the temperature remains between 15°C and 35°C with no fluctuations.

In the presence of a newly-applied top layer of plaster.

Make sure that the base is solid and dry and that there is no mould or rising damp. Apply an extra-fine, white-coloured, smooth skim finish to the entire surface using a suitable cement-based skim coat. To even out absorption and improve adhesion, apply one or two coats of acrylic primer in an aqueous dispersion suitably diluted as recommended by the manufacturer. Wait until this is dry before proceeding to apply GlamSatin.

In the presence of existing plasterwork or a slightly uneven base.

Sand and remove any material that is coming off as well as any salty deposits and old peeling paint. Carefully clean the base using suitable equipment and make sure it is completely dry, even and flat. Apply an extra-fine, white-coloured, smooth skim finish to the entire surface using a suitable cement-based skim coat. To even out absorption and improve adhesion, apply one or two coats of acrylic primer in an aqueous dispersion suitably diluted as recommended by the manufacturer. Wait until this is dry before proceeding to apply GlamSatin.

In the presence of a ceramic wall covering or tiles.

Carefully clean the surface using suitable equipment for ceramic or tiles and remove any traces of limescale. Make sure that the wall is completely dry. Apply a thin, light-coloured, smooth skim finish using a suitable (preferably cement-based) skim coat. Once this is dry, apply a second extra-fine, white-coloured, smooth skim finish using a suitable cement-based skim coat. To even out absorption and improve adhesion, apply one or two coats of acrylic primer in an aqueous dispersion suitably diluted as recommended by the manufacturer. Wait until this is dry before proceeding to apply GlamSatin.

4. Technical characteristics

DIMENSIONS:	
Roll width	50 cm 19.68 in
Roll length	custom
Weight	470 (+/- 20) g/m ² 1.54 (± 0.06) oz/sq ft
Thickness	0,46 mm 0.018 in
Appearance	Silky
Composition	Viscose 57% Resin and mineral content 25% Non-woven fabric 18%
Reaction to fire (UNI EN 13501-1)	Euro class: B-s1, d0
Washability	Washable. See instructions in point 6 "Cleaning and care"

5. Certifications

FSC®	FSC-C100728
Chemical safety certification	OEKO-TEX® – Standard 100
Equivalent to:	
– Annex XVII di REACH	
– CPSIA	
– Chinese standard GB 18401:2010	

6. Cleaning and care

Before cleaning your wallcovering, it is recommended that you read the manual *Care and Maintenance Advice*, which can be downloaded from the *Materials* page of glamora.it. Should you require further details, please contact our Customer Care Service.

GlamSatin is a washable wallcovering. Due to its natural fibres, it must be handled with the utmost care. If the wallcovering does get marked, gently dab it to immediately remove any mark or stain from the surface. Use a non-abrasive damp sponge or a damp microfibre cloth rinsed in clean, lukewarm water. Do not rub.

Glamora is not responsible for any damage caused during cleaning.

7. Warnings

- Product for professional use.
- Follow the national regulations.
- Make sure that the surface is perfectly clean, dry and planar.
- If necessary, require the safety data sheet.
- For any information that is not provided, please consult the Glamora assistance service T +39 0536.076.403 – contact@glamora.it

The application of Glamora wallcoverings to surfaces other than those specifically indicated in the manuals or in the company's official installation videos (for example wood, laminate, metal, resin or similar materials) or for uses other than that for which the wallcovering was designed (for example installation on the floor, doors, panels, outdoors or in similar environments) does not comply with the manufacturer's instructions. Therefore, in such cases, any warranty issued to the purchaser will be null and void and Glamora Srl will accept no contractual or extra-contractual liability for the same, nor shall it be answerable for any product defects and/or differences in performance detected as a result. In such cases, the product will be considered as having been sold at the risk and peril of the buyer and Glamora Srl will be under no obligation, nor will it be responsible for upholding any warranty. Without prejudice to the above, and subject to you sharing the relative technical characteristics, Glamora Srl may provide suggestions regarding the treatment of your installation surfaces, but only as a form of mere courtesy and without accepting any liability, upon your request. In the event of you requesting suggestions and/or subsequently passing a purchase order, it will be considered that the parties are aware of the conditions stated above and that you have specifically acknowledged and accepted these.