



Discover the stylish, versatile and aesthetic freestyle

The Soundtect Ripple: Gently curved semi circular tubes of superior acoustic felt, affixed to walls for a stunning rippled wall effect, with superb acoustic qualities.

The easily installed design is suited to a range of commercial applications and ensures effective acoustic management whatever the space. Each strip, up to a maximum 2400mm length, can be cut into various widths of choice.

Soundtect recommends a selection of 30mm, 60mm and 100mm (as shown) for a truly stunning feature.

With up to 70% recycled content and finely tuned reverberation and sound control, Freestyle™ is the natural choice for acoustic designs that challenge the status quo.

Developed by London-based Soundtect®, Freestyle™ panels are built to exacting quality and use all Soundtect's pioneering acoustic know-how.

KEY FEATURES & BENEFITS

- Elevated design potential
- Incredible versatility
- Available in 24 colours
- Create bespoke designs in specific corporate or design colours
- **installed on the walls to create a harmonious finish with superb sound control properties**
- Excellent sound absorption
- Finely tuned reverberation thanks to Soundtect's pioneering acoustic technology
- Environmentally friendly and recyclable, Freestyle™ Acoustic Panels are ideal for projects when there is an eco-conscious consideration to be made
- Manufactured by Soundtect®
- Independently certified

freestyle

Colour range



Product Specifications

TYPICAL APPLICATIONS

Wall Coverings

- Composition: 100% Polyester
- Low VOC
- Colour Fastness Properties
 - Colorfastness to Light, AATCC16(3), Class 4.5
- ISO 14006 Certified Manufacturing Facility
- Certified 100% Recyclable
- Recycled Content: Up to 70% (min. 50% post consumer recycled content)

FIRE RATING

- EN13501, Bs1d0

SIZE

- 30 x 2400mm
 - 60 x 2400mm
 - 100 x 2400mm
- More sizes available on request

DENSITY THICKNESS

- 10mm, 2kg/sqm
- 20mm, 4kg/sqm

INSTALLATION

- Wall mounted Freestyle™ coverings,

Moisture Absorption

Polyester fibre when exposed to an atmosphere of 50°C at 90% relative humidity for four days showed moisture absorption of less than 0.03% by weight. Polyester is not affected by moisture.

Does not contain any Red List chemicals*.