

Declaration of Performace

According to Regulation (EU) No 305/2011 of 9 March 2011

 $N^{\circ}: 2013/1$

	1	Product type for identification	Dry-pressed ceramic tiles with low water absorption of $E_b \le 0.5\%$
\prod	2	Intended use	For floor and wall coverings in indoor and outdoor areas
	3	Manufacturer	CE.SI. – Ceramica di Sirone S.r.l, via Don Minzoni ,19 Sirone
	4	System of assessment and verification of constancy of performance	System 3 and 4
	5	Name and number of the office for the control	Centro Ceramico di Bologna, via Martinelli 26, Bologna –N°1477

6 Declared performace

Essential characteristics	Performance	Harmonized technical specification	
Behaviour in fire	Classe A1 _{FL} /A1	EN 14411 : 2012	
Flexural tensile strength	> 1300 N (thickness ≥ 7,5 mm)	EN 14411 : 2012	
riexurai tensne strength	> 700 N (thickness < 7,5 mm)	EN 14411 . 2012	
Non – slip properties *	R13	EN 14411 : 2012	
Tactility **	NPD	EN 14411 : 2012	
Thermal shock resistence	Resistence	EN 14411 : 2012	
adhesive strength:			
Mortars containing cement type C2	$\geq 1 \text{ N/mm}^2$	EN 14411 : 2012	
Durability in case of:			
Application in indoor areas	Resistence	EN 14411 : 2012	
Application in outdoor areas	Resistence	EN 14411 : 2012	
Delivery of dangerous substances:			
Cadmium***	Don't release	EN 14411 : 2012	
Lead ***	Don't release	EN 14411 : 2012	
VOC	A+	EN ISO 16000-:2012-03-01	

^{*} Necessary only when expressly required of the official regulations. For details refer to the pages of the catalogue

The performace of the product identified in point 1 is in conformity with the declared performace in point 6 This declaration of performace is issued under the sole responsability of the manufacturer identified in point 3

Signed for and on behalf of the manufacturer by:

Fumagalli Federico Name and function

Sirone, 01/01/2016

^{**}Only if it is necessary a surface with tactile effect or for blind people

^{***} Only needed if the material is in contact with food or when expressly required of the official regulations