

## ALELUIA CERÂMICAS

## DECLARATION OF PERFORMANCE Nr. 5 (UKCA/DDP 5)

1 – Identification of the Product – Ceramic pressed floor tiles - Group BIa (E  $\leq$  0,5 %) – GL (Glazed) – Norm EN 14411:2012 (Annex G)

2 – Type – All sizes of porcelain floor tiles - Thickness  $\geq$  7,5 mm

## 3 – Intended use – Floor and Wall coverings for indoors and outdoors

**4 - Manufacturer Identification:** Aleluia Cerâmicas S.A. Quinta do Simão - Esgueira 3801-101 - Aveiro - Portugal Apartado 3024 Telefone : + 351 234 305 600 Fax + 351 234 305 699 Email: <u>geral@aleluia.pt</u>

- 5 Not applicable
- 6 System of Assessment / Verification 4
- 7 Not applicable
- 8 Not applicable
- 9 Declaration of Performance

PRODUCT: Ceramic Pressed Floor Tiles - EN 14411: 2012 - Group Bla (Annex G) – GL Thickness ≥ 7,5 mm				
Characteristics		Declared Values	Test Method	Norm
Reaction to Fire		Classe A1fl		With no Test Reg. EU nº 305/2011
Mechanical Resistance Flexion Resistance		≥ 1300 N In Conformity	EN ISO 10545 - 4	
Mechanical Resistance Modulus of Rupture		≥ 35 N/mm2 In Conformity		
	Internal Use	In Conformity		
Durability	External Use - Frost Resistance	In Conformity	en ISO 10545 – 12	EN 14411:2012
Thermal Shock Resistance		In Conformity	EN ISO 10545 – 9	
Slipping (Friction Coefficient)		NPD		
Anti-Slippping (for vehicles circulation)		NPD		
Emission of dangerous substances (Cd and Pb)		NPD		
Gluing Resistance / Adherence		NPD		

The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9.

The present declaration is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

the

Elmano Castilho (Quality and Ambient Director)

Aveiro, 31th October 2022

Código: FR VEN 604 Edição: 1 Revisão: 0 Data: Outubro 2022

